

Multimodal Explainable AI Models for Clinical Reasoning





Assistant Professor

Computer Science | Virginia Tech

Perception and LANguage (PLAN) Lab

https://isminoula.github.io/







Progress in AI/ML Adoption



Source: https://dribbble.com/shots/6781718-Smartwatch by Laurens van Vliet




Source: https://www.fastcompany.com/3045397/how-cars-aremade-in-20-gifs



Source: https://ochin.org/telehealth

Key ML Ingredients









Source: https://research.aimultiple.com/gpt/

What do NNs really learn?



A herd of sheep grazing on a lush green hat Tags: grazing, sheep, mountain, cattle,




NeuralTalk2: A flock of birds flying in the air
Microsoft Azure: A group of giraffe standing next to a tree

Image: Fred Dunn, https://www.flickr.com/photos/gratapictures - CC-BY-NC

Source: https://www.aiweirdness.com/do-neural-nets-dream-of-electric-18-03-02/

What do NNs really learn?

as compared to the previous radiograph, there is no relevant change. tracheostomy tube is in place. there is a layering pleural effusions. NAME bilateral pleural effusion and compressive atelectasis at the right base. there is no pneumothorax.



How can we gain confidence and trust in machine learning models deployed in healthcare?

CXR report generation [1]


Challenges with ML models

Limited Information

Models are not aware of anything else other than what is in their input data

Verifiable & Trustworthy Information

Non-trivial to sanitize (and trust) output of an ML model



Source: https://datascience.stackexchange.com/questions/42621/data-science-related-funny-quotes

Current Medical Imaging Datasets

Existing Chest X-Ray (CXR) datasets


| Dataset | Annotation Level | Annotation Method | Num Labels | Anatomy Labeled | Graph | Dataset Size | Temporal Labels | Reports |
|--|-----------------------|--------------------|------------|-----------------|-------|--------------|-----------------|---------|
| SIIM-ACR Pneumothorax Segmentation [13] | Segmentation | Manual + augmented | 1 | No | No | 12,047 | No | No |
| RSNA Pneumonia Detection Challenge [38] | Bounding Boxes | Manual | 1 | No | No | 30,000 | No | No |
| Indiana University Chest X-ray collection [12] | Global | Automated | 10 | No | No | 3,813 | No | Yes |
| NIH CXR dataset [42] | Global | Automated | 14 | No | No | 112,120 | No | No |
| PLCO [40] | Global | Automated | 24 | Yes | No | 236,000 | Yes | No |
| Stanford CheXpert [20] | Global | Automated | 14 | No | No | 224,316 | No | No |
| MIMIC-CXR [22] | Global | Automated | 14 | No | No | 377,110 | No | Yes |
| Dutta [10] | Global | Manual | 10 | Yes | Yes | 2,000 | No | Yes |
| PadChest [5] | Global | Manual + automated | 297 | Yes | No | 160,868 | No | Yes |
| Montgomery County Chest X-ray [21] | Segmentation | Manual | 1 | Yes | No | 138 | No | No |
| Shenzen Hospital Chest X-ray [21] | Segmentation | Manual | 1 | Yes | No | 662 | No | No |
| Chest ImaGenome | Bounding Boxes | Automated | 131 | Yes | Yes | 242,072 | Yes | Yes |

- **Existing datasets** focused on supporting classification, text generation, single abnormality detection or segmentation problems
- **Chest ImaGenome** Longitudinal Visual Genome-like dataset Supports classification, text generation, multiple abnormality detection, temporal comparison and anatomically aware clinical reasoning problems. Automatically generated with a dual-validated subset.

Chest ImaGenome

Longitudinal Scene Graph Dataset that simplifies anatomically aware clinical reasoning:

- **242,072** graphs
- 29 object types
- 76 attribute types
- 4.9M relations




[2] Wu, J.T., Agu, N.N., Lourentzou, I., Sharma, A., Paguio, J.A., Yao, J.S., Dee, E.C., Mitchell, W.G., Kashyap, S., Giovannini, A. and Celi, L.A., Chest ImaGenome Dataset for Clinical Reasoning. NeurIPS Datasets and Benchmarks Track (2021)

Object-attribute relations

{right lung} has {chest tube}

- 29 CXR anatomical objects
- 76 attribute types
- 6 semantic categories
- 1256 unique types of object-to-attribute relations
- 4.3M object-attribute relations
- Embedded parent-child & child-parent relations



[2] Wu, J.T., Agu, N.N., Lourentzou, I., Sharma, A., Paguio, J.A., Yao, J.S., Dee, E.C., Mitchell, W.G., Kashyap, S., Giovannini, A. and Celi, L.A., Chest ImaGenome Dataset for Clinical Reasoning. NeurIPS Datasets and Benchmarks Track (2021)

Object-attribute relations

One clinical question per scene grap

242,072 graphs


Other Clinical Q's:

Where is A?

J. Does Obj have A?


Is A1 associated with A2 at Obj?

Has (Obj,t) {C} since (Obj,t-1)?
C = {improved, worsened, no change}



[2] Wu, J.T., Agu, N.N., Lourentzou, I., Sharma, A., Paguio, J.A., Yao, J.S., Dee, E.C., Mitchell, W.G., Kashyap, S., Giovannini, A. and Celi, L.A., Chest ImaGenome Dataset for Clinical Reasoning. NeurIPS Datasets and Benchmarks Track (2021)

Anatomy-aware X-ray Network (AnaXNet)




AnaXNet [3]: We extract anatomical regions of interest (ROIs) and their corresponding features, feed their vectors to a Graph Convolutional Network that learns their inter-dependencies, and combine the output with an attention mechanism, to perform the final classification with a dense layer.



Anatomy-aware X-ray Network (AnaXNet)

Comparison against baselines (AUC scores)

| Method | L1 | L2 | L3 | L4 | L5 | L6 | L7 | L8 | L9 | AVG |
|----------------|------|------|------|------|------|------|------|------|------|------|
| Faster R-CNN | 0.84 | 0.89 | 0.77 | 0.85 | 0.87 | 0.77 | 0.75 | 0.81 | 0.71 | 0.80 |
| GlobalView | 0.91 | 0.94 | 0.86 | 0.92 | 0.92 | 0.93 | 0.86 | 0.87 | 0.84 | 0.89 |
| CheXGCN | 0.86 | 0.90 | 0.91 | 0.94 | 0.95 | 0.75 | 0.89 | 0.98 | 0.88 | 0.90 |
| AnaXNet (ours) | 0.88 | 0.96 | 0.92 | 0.99 | 0.95 | 0.80 | 0.89 | 0.98 | 0.97 | 0.93 |



Enlarged cardiac silhouette example



Object-Object Comparison Relations

Classify disease progression over two sequential CXR exams


Over 670k localized comparison relations


Clinical Question: Has (Obj,t) {C} since (Obj,t-1)?

Comparison relations


C = {improved, worsened, no change}

- **Objects:** anatomical regions, such as. 'left lung' 'right lung', etc.
- **Attributes**: anatomical findings, such as 'pulmonary edema/hazy opacity', 'fluid overload/heart failure', etc.






CheXRelNet: Object-Object Comparison Relations




- Incorporate local and global visual features
- Capture intra-image region-disease co-occurrences
- Capture inter-image region-based disease progression
 Learn dependencies between anatomical region attributes
 to accurately predict disease progression




Results: Object-Object Comparison

Comparison against baselines (accuracy)

| Method | D1 | D2 | D3 | D4 | D5 | D6 | D7 | D8 | D9 | All |
|-------------------------------|------|------|------|------|------|------|------|-----------------------------|------|------|
| Local Global CheXRelNet | 0.67 | 0.69 | 0.64 | 0.74 | 0.71 | 0.50 | 0.65 | 0.47 0.69 0.73 | 0.67 | 0.67 |






CXR 1 CXR 2


Pathology Fluid Overload/Heart Failure, class: Worsened



Utilizing Eye Gaze




Eye tracking heatmaps for driver's attention



Consumer research [5]



Eye tracking traffic control room operators [6]



Eye gaze in CT [7]

Fairly unbiased view of what the humans are looking for in a scenario


Motivated by the high resemblance of activation maps used in deep learning for saliency with gaze fixation studies for other fields.

- [5] https://phys.org/news/2012-07-consumer-product-giants-eye-trackers-size.html
- [6] https://www.tobiipro.com/applications/scientific-research/case-studies/university-birmingham/
- [7] Khosravan, N., Celik, H., Turkbey, B., Jones, E.C., Wood, B. and Bagci, U., A collaborative computer aided diagnosis (C-CAD) system with eye-tracking, sparse attentional model, and deep learning. Medical image analysis, 2019

Utilizing Eye Gaze in Radiology


Can we imitate the radiologist with attention supervision? Utilize eye gaze information to

- Train better radiology models
- Improve interpretability
- Incorporate domain knowledge without explicit pixel-level labels






Data Sample




Radiology Report: Left-sided cardiac defibrillator with leads projecting over the right atrium and ventricle. Cardiomegaly. Aortic calcifications. Left-sided pleural effusion with atelectasis. prominent right breast shadow. The lungs appear hyper-inflated suggesting COPD. There is some scarring at the right base.

Data Sample

- Eye gaze data
- Audio (synced with eye gaze)
- Transcript (time-stamped)
- Bounding boxes of anatomies 17 anatomical regions
- Segmentation maps of key anatomies


















ML Experiment #1: Temporal Gaze as Input









ML Experiment #2: Static Gaze as Output


CHF: Gaze fixations increase around the hilar and heart region



Pneumonia: Gaze fixations focus on the lung opacity



Normal: Gaze fixations skip around the image.








[8] Karargyris, A., Kashyap, S., Lourentzou, I., Wu, J.T., Sharma, A., Tong, M., Abedin, S., Beymer, D., Mukherjee, V., Krupinski, E.A. and Moradi, M., Creation and validation of a chest X-ray dataset with eye-tracking and report dictation for Al development. Nature Scientific data (2021)


https://tinyurl.com/EyeGaze2021

To summarize ...









ML still fails to see the bigger picture



Under-specification: Average case model performance on fixed test data

Data routinely collected might be influenced by social, institutional, and other types of biases

ML decisions cannot be same across all users

Source: https://blog.pepid.com/wp-content/uploads/2018/05/RobotsForNursesHero.png

When designing new ML methods, we need to be able to ...



Source: https://blog.pepid.com/wp-content/uploads/2018/05/RobotsForNursesHero.png

- ✓ Identify failure modes: worst-case performance
- ✓ Systematically assess model AND data quality
- ✓ Explicitly control for various biases
- ✓ Incorporate ways to define and assess model behavior when deployed in the real-world, when no groundtruth data are available

Thank you to...



Gaurang Karwande



Amarachi Mbakwe



Leo A. Celi



Joy T. Wu



Alexandros Karargyris







Nkechinyere N. Agu



Satyananda Kashyap



Mehdi Moradi



Pingkun Yan



James Hendler



https://tinyurl.com/AnaXNet2021

Perception and LANguage (PLAN) Lab @VT

https://plan-lab.github.io/

Anaxnet: Anatomy aware Multi-label 👺 Finding Classification in Chest X-ray





















https://tinyurl.com/CheXRelNet

CheXRelNet: An Anatomy-Aware Model for Tracking Longitudinal Relationships between Chest X-Rays (MICCAI 2022)





https://tinyurl.com/EyeGaze2021

Creation and Validation of a Chest X-ray Dataset with Eye-Tracking and Report Dictation for AI Development.